

<b>Product Definition</b>	<b>9000 Btu/h Split EU A++ /A+ Inverter with kit</b>
Arcelik Model Name	<b>BRVPG 090 / BRVPG 091</b>
Brand	<b>Beko</b>
EAN CODE	<b>8690842185199/ 8690842185175</b>
STOCK CODE	<b>8869643200</b>
<b>Main Features</b>	
Indoor Unit Chassis Color & Material	Itanium steel grey HIPS
Front Panel Color & Material	White HIPS
Outlet Grille Color & Material	White HIPS
Refrigerant	R32
Total Refrigerant Amount (g)	500
Climate Class	T1
Heating Type	Heat Pump
Power Supply Connection	Outdoor
<b>Product Definition</b>	
Filters	High Density Filter*2pcs
Extra Filters	silver ion filtern Filter*1pc bio filter Filter*1pc
Remote Control	LCD
Digital_Display	LED
Jet Cool	Yes
Jet Heat	Yes
Auto-Restart Function	Yes
Dehumidifying Function	Yes
Automatic Temperature Control	Yes
Sleep Mode	Yes
Timer Function	24hour
Defrost Function	Yes
Fan Speed Steps	Turbo/H/M/L/Auto
Hotstart	Yes
Automatic Air Direction (Up-Down)	Yes
Self Clean+ Function	Yes
Auto-Changeover	Yes
"ZoneFollow" Function	Yes
<b>Main Performance</b>	
Cooling Capacity (Btu/h)	8871(Pdesign C)
Adjustable Cooling Capacity Range (Btu/h)	3100-10600
Cooling Capacity (W)	2600(Pdesign C)
Adjustable Cooling Capacity Range (W)	908~3106
Heating Capacity (Btu/h)	7165(Pdesign H)
Adjustable Heating Capacity Range (Btu/h)	2800-11500
Heating Capacity (W)	2100(Pdesign H)
Adjustable Heating Capacity Range (W)	820~3337
SEER/AEER/Weight EER (W/W)	6.2 (SEER, EU)
SCOP/ACOP/Weight EER (W/W)	4.0 (SCOP, EU Average Season)

Energy Level-Cooling	A++
Energy Level-Heating	A+
Cooling Power Input (W)	710
Heating Power Input (W)	739
Voltage/Frequency (V/Hz)	220-240V~ 50Hz, 1Ph
Noise Power Level - Indoor Unit (dBA) - (Sound Power)	53
Noise Power Level - Outdoor Unit (dBA) (Sound Power)	61
Noise Pressure Level - Indoor Unit (dBA) (Sound Pressure)	40/30/26/21
Noise Pressure Level - Outdoor Unit (dBA) (Sound Pressure)	56
Air flow volume ( m3/h )	520/460/340
Moisture removal (L/H.r)	1
Max. elevation (m)	10
Max. pipe length (m)	25
Ambient Working Temperature Range(°C) Cooling-Outdoor	-10 ~ 50
Ambient Working Temperature Range(°C) Heating-Outdoor	-10 ~ 30
<b>Logistics Data</b>	
Indoor Unit (WxDxH) mm	805x194x285
Outdoor Unit (WxDxH) mm	700x275x550
Indoor Unit Net Weight (kg)	7,5
Outdoor Unit Net Weight (kg)	23
Packed Indoor Unit ( WxDxH ) mm	870x270x360
Packed Outdoor Unit ( WxDxH ) mm	815x350x615
Indoor Unit Weight - Packed (kg)	9,7
Outdoor Unit Weight - Packed (kg)	27
40'HQ Container Loading Quantity(with kit)	264
40'GP Container Loading Quantity(with kit)	220
20' Container Loading Quantity(with kit)	100
<b>Accessories</b>	
Connection copper pipe length (m)	3m
Communication cable length (m)	3.5m
Power cable length (m)	3.5m(packed in Indoor unit)
Water draining pipe length (m)	0,538
Insulating material	PE
Remote Control Battery	Yes
Installation Kit	
Installation Kit- Wall Mounting Screw&Bolts	Yes
Installation Kit- Additional Drainage Hose	Yes
Installation Kit- Bandage Tape	Yes
Installation Kit- Anti-Vibration Rubber Feet	Yes
Installation Kit- Wall Hole Plastic Cover	Yes
Installation Kit- Outdoor Drainage Nut	Yes
Installation Kit- Copper Pipe Nut	Yes

<b>12000 Btu/h Split EU A++/A+ Inverter with kit</b>
<b>BRVPG 120 / BRVPG 121</b>
<b>Beko</b>
<b>8690842185212/ 8690842185205</b>
<b>8869663200</b>
Itanium steel grey HIPS
White HIPS
White HIPS
R32
500
T1
Heat Pump
Outdoor
High Density Filter*2pcs silver ion filtern Filter*1pc bio filter Filter*1pc
LCD
LED
Yes
Yes
Yes
Yes
Yes
Yes
Yes
Yes
24hour
Yes
Turbo/H/M/L/Auto
Yes
Yes
Yes
Yes
Yes
11942(Pdesign C)
3800~14200
3500(Pdesign C)
1113~4161
7848 (Pdesign H)
3700~14400
2300(Pdesign H)
1084~4220
6.1 (SEER, EU)
4.0 (SCOP, EU Average Season)

